

GIADA FS MODEL

**REPORT ON
THE COMET ESCORT 1 PHASE
21/11/2014 - 10/03/2015**

PREPARED	APPROVED	AUTHORIZED
GIADA TEAM A. ROTUNDI, V. DELLA CORTE, R. SORDINI INAF – Istituto di Astrofisica e Planetologia Spaziali, Roma (I) Università Parthenope, Napoli (I)	GIADA PI A. ROTUNDI	GIADA PI A. ROTUNDI

TABLE OF CONTENTS

<u>1.</u>	<u>SCOPE AND APPLICABILITY</u>	<u>5</u>
<u>2.</u>	<u>REFERENCES</u>	<u>6</u>
	2.1 APPLICABLE DOCUMENT	6
	2.2 REFERENCE DOCUMENT	6
<u>3.</u>	<u>DEFINITIONS AND ABBREVIATIONS</u>	<u>7</u>
	3.1 ABBREVIATIONS	7
<u>4.</u>	<u>DESCRIPTION OF ACTIVITIES</u>	<u>9</u>

REVISIONS LOG

REV	DOCUMENT CHANGE ORDER	DATE	CHANGES DESCRIPTION	PREPARED
0	-	23-10-2015	First issue	GIADA Team

1. SCOPE AND APPLICABILITY

The Comet Escort 1 Phase covers the period of time from the 21st November 2014 until the 10th March 2015. It started after Rosetta successfully completed the Prelanding Phase. The GIADA data collected in the present DataSet are complete and follow, without time interruption, the data of Prelanding DataSet (RO-C-GIA-3-PRL-PRELANDING-V1.0). This document reports the configurations used by GIADA FS during Comet Escort Phases 1. This report refers to the GIADA FS model on board the Rosetta S/C. The data were retrieved from DDS by means of the PI Workstation located at Istituto di Astrofisica e Planetologia Spaziali in Rome. We used the MaGx Converter v. 3.0 software on GIADA IWS to convert the DDS data. GIADA in flight software configuration is 2.3 plus three additional patches (one more patch is used to update the context file).

2. REFERENCES

2.1 APPLICABLE DOCUMENT

AD1	RO-EST-RS-3001/EID A	ROSETTA Experiment Interface Document – Part A
AD2	RO-EST-RS-3009/EIDB	ROSETTA GIADA Experiment Interface Document – Part B
AD3	RO-ESC-PL-5000 – last issue	Flight Control Procedure
AD4	GIA-GAL-MA-007 Issue 4	GIADA Flight Spare Experiment User Manual last version

2.2 REFERENCE DOCUMENT

	None.	

3. DEFINITIONS AND ABBREVIATIONS

3.1 ABBREVIATIONS

CAL	Calibration
CF	Context File
CREP	Cover REPort
CT	Configuration Table
DDS	Data Disposition System
EGSE	Electrical Ground Support Equipment
EQM	Electrical Qualification Model
ESA	European Space Agency
FCP	Flight Control Procedure
FS	Flight Spare
GDS	Grain Detection System
GES	GIADA EGSE SW
GIADA	Grain Impact Analyser and Dust Accumulator
HK	House Keeping
I/F	InterFace
INAF-OAC	INAF - Osservatorio Astronomico di Capodimonte – Napoli (I)
INAF-IAPS	INAF-Istituto di Astrofisica e Planetologia Spaziali – Roma (I)
IRQ	Interrupt ReQuest
IS	Impact Sensor
IWS	Instrument Work-Station
MBS	Micro Balance System
ME	Main Electronics
MTL	Mission TimeLine
MON	Monitor
OBCP	On-Board Control Procedure
PC	Payload Checkout
PDOP	Payload Direct Operations Proposal
PI	Principal Investigator
PS	GIADA Power Supply
PZT	(IS) Piezoelectric Sensor
RED	Redundant
REV	Revision
RMOC	Rosetta Mission Operation Centre
RSOC	Rosetta Science Operation Centre
S/C	(Rosetta) Spacecraft
S/S	(GIADA) Sub-system (e.g. IS or GDS or MBS)
SAA	Solar Aspect Angle ¹
SCI	Scientific
SSC	Source Sequence Count
SSMM	Solid State Mass Memory on-board of Rosetta Spacecraft

¹ The angle formed between the spacecraft Z-axis and the Sun direction in the XZ plane (Della Corte et. Al. 2014, present in “Document” folder).

STP	Short Term Plan (1 week of operations)
SW	Software
TC	TeleCommand
THS	Threshold
TM	Telemetry
UM	User Manual
UTC	Coordinated Universal Time
VC0	Virtual Channel 0 (Real Time TM packets)
VC1	Virtual Channel 1 (TM packets coming from Mass Memory)

4. DESCRIPTION OF ACTIVITIES

The Comet Escort 1 Phase (ESC1) identifies the period of time from the 21st November 2014 until the 10th March 2015. It started after Rosetta successfully completed the Prelanding Phase.

In the following table there is some information about the Comet Escort 1 Phase

Scenario period	Start 21-11-2014	End 10-03-2015
Scenario duration	110 days	
Sun distance	~ 2.92 AU	~ 2.10 AU
Earth distance	~3.46AU	~3.03AU
Propagation delay	~28 min 47s.	~25 min 13s.

The configurations of GIADA during the ESC1 Phase are described at STP level in Table 1. Here are reported a short description and the anomalies, if occurred.

STP	Date [UTC]	Conf.	Description	Notes/Anomalies
0029	Start 18-11-2014 23:25:00 End 21-11-2014 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) every 6h. A GIADA switch off w/o Close Cover was performed at the end of STP.	Note that the data by 20 November are collected in the Prelanding DataSet (RO-C-GIA-3-PRL-PRELANDING-V1.0).
030	Start 21-11-2014 23:25:00 End 25-11-2014 23:24:59	Normal Main I/F	GIADA switched on and a Context File with new GDS THS (Left: 1.7V, Right: 1.3V) was uploaded. GIADA went in Normal Mode. Switch of IS Range (Low/High) performed every 6h.	The new THS values are set in order to reduce the noise of the GDS receivers due to a small contamination.
031	Start 25-11-2014 23:25:00 End 02-12-2014 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h without any actions during Consert's opportunity window.	
032	Start 02-12-2014 23:25:00 End 09-12-2014 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h. On 5/12 the GDS Left THS changed taking into account Sun Aspect Angle (SAA).	
033	Start 09-12-2014 23:25:00 End 16-12-2014 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h. GDS switched Off/On taking into account SAA.	

034	Start 16-12-2014 23:25:00 End 19-12-2014 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h, GDS switched Off considering SAA.	
035	Start 19-12-2014 23:25:00 End 23-12-2014 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h, GDS switched On at the beginning of STP.	On 20-12-2014 at 4:30 there was an excessive increase of the GIADA data rate, due to some contamination on the GDS Left channel. In order to fix this issue a PDOP file was sent to RMOC (23-12-2014) to increase the GDS Left THS (4.0V). This DataSet contains only the HK data for the period from 20 at 4.30 till 24 December 2014.
036	Start 23-12-2014 23:25:00 End 30-12-2014 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h.	Because of the issue occurred on 20/12 and fixed by increasing the GDS Left THS on 23/12, this DataSet contains only the HK data from 20 at 4.30 till 24 December 2014.
037	Start 30-12-2014 23:25:00 End 06-01-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) every 6h. On 3-01-2015 the GDS THS changed taking into account SAA.	Because of the issue occurred in STP035, fixed by increasing the GDS Left THS we had to update the the GDS Left THS after the changes of the THS values performed in STP037. We sent a PDOP file to RMOC (on 29/12) to set the updated value.
038	Start 06-01-2015 23:25:00 End 13-01-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h. MBS Heating when Sun saturates the GDS Receivers.	
039	Start 13-01-2015 23:25:00 End 20-01-2015 23:24:59	Normal Main I/F	GIADA went in Safe Mode and a Context File with a new GDS Left THS (Left: 4.0V, Right: 1.3V) was uploaded. GIADA went in Normal Mode, Switch of IS Range (Low/High) performed every 6h.	

040	Start 20-01-2015 23:25:00 End 27-01-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h.	
041	Start 27-01-2015 23:25:00 End 03-02-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h. GDS THS changed taking into account SAA. MBS Heating when Sun saturates the GDS Receivers. The IS Autogain was enabled.	
042	Start 03-02-2015 23:25:00 End 10-02-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h. GDS THS changed taking into account SAA.	
043	Start 10-02-2015 23:25:00 End 17-02-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h. During the Fly-by: IS Range set to Low.	
044	Start 17-02-2015 23:25:00 End 24-02-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of Range (Low/High) performed every 6h. MBS Heating when Sun saturates the GDS Receivers.	
045	Start 24-02-2015 23:25:00 End 03-03-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h.	
046	Start 03-03-2015 23:25:00 End 10-03-2015 23:24:59	Normal Main I/F	GIADA in Normal Mode, Switch of IS Range (Low/High) performed every 6h.	

Table 1: GIADA Operations during the Comet Escort 1 Phase

The data were elaborated off-line on the PI IWS at INAF-IAPS in Rome.
During the Comet Escort 1 Phase the GIADA Cover has never been activated.